

# calypso™

## EP Glider



## Cruise on air

Smooth and forgiving, the Calypso excels as a first electric sailplane. Experienced glider pilots will enjoy its wide range of soaring performance, and may elect to use the optional flaps for more advanced thermal chasing. Three versions — the RTF, Tx-R and Rx-R — include a factory-installed brushless power system and require only a screwdriver for final assembly.

- Features durable AeroCell foam construction.
- Two-piece wing removes easily for transport.
- Independent aileron servos allow mixing.
- Large on-board compartment accepts a variety of batteries.
- Bold green and black trim stands out at high altitudes.
- Includes integrated landing wheel plus nose and tail skid plates.

### Calypso specifications:

Wingspan: 73 in (1855 mm)    Wing Area: 526 in<sup>2</sup> (33.9 dm<sup>2</sup>)    Length: 47 in (1195 mm)



### FLZA3000

**RTF Weight:** 29 oz (820 g)  
**Wing Loading:** 7.9 oz/ft<sup>2</sup> (24 g/dm<sup>2</sup>)  
**Includes:** Tactic TTX404 4-channel 2.4GHz SLT radio system; factory-installed 28-30-1300kV brushless outrunner motor, 18A ESC, SLT receiver & servos; 11.1V 1300mAh 15C LiPo battery; AC/DC balancing charger & (5) "AA" batteries



### FLZA3002

**RTF Weight:** 29 oz (820 g)  
**Wing Loading:** 7.9 oz/ft<sup>2</sup> (24 g/dm<sup>2</sup>)  
**Includes:** factory-installed 28-30-1300kV brushless outrunner motor, 18A ESC, SLT receiver & servos; 11.1V 1300mAh 15C LiPo battery; AC/DC balancing charger & (5) "AA" batteries  
**Requires:** 4-5 channel SLT transmitter — or — AnyLink2 & compatible 4-5 channel radio



### FLZA3004

**RTF Weight:** 29-31 oz (820-880 g)  
**Wing Loading:** 7.9-8.5 oz/ft<sup>2</sup> (24-26 g/dm<sup>2</sup>)  
**Includes:** factory-installed 28-30-1300kV brushless outrunner motor, 18A ESC & servos;  
**Requires:** 4-5 channel transmitter & receiver, 11.1V 1300mAh LiPo battery & LiPo charger



### FLZA3006

**RTF Weight:** 29-31 oz (820-880 g)  
**Wing Loading:** 7.9-8.5 oz/ft<sup>2</sup> (24-26 g/dm<sup>2</sup>)  
**Requires:** 4-5 channel transmitter & receiver, servos, 28-30-1300kV brushless outrunner motor, 18A ESC (min.) 11.1V 1300mAh LiPo battery & LiPo charger

### Recommended Products (for Tx-R, Rx-R & ARF versions)

**TACJ2650** Tactic TTX650 6-Channel 2.4GHz SLT Computer Transmitter — or —  
**FUTK6000** Futaba 6J 6-channel 2.4GHz S-FHSS Computer Radio System and  
**TACJ2005** Tactic AnyLink2 2.4GHz Radio Adapter  
**FLZA6014** Flyzone 11.1V 1300mAh LiPo Battery (Rx-R & ARF only)  
**GPMM3318** ElectriFly AC/DC Balancing Smart Charger (Rx-R & ARF only)  
**TACL0624** Tactic TR624 4-Channel 2.4GHz SLT Receiver (Rx-R & ARF only)

### Recommended Options

**FLZA6008** Calypso Flap Linkage Set (Requires 5-channel radio)  
**GPMM3155** ElectriFly Triton EQ AC/DC Balancing Charger  
**SUPM0040** SuperTigre Adapter Star Plug to SuperTigre ESC

