

Acro-Wot™ MkII

pure sport fun



Sport flying at its best

The Acro-Wot MkII combines the best in contemporary looks, modern construction and classic sport performance. The lightweight, molded AeroCell foam airframe offers outstanding durability, and carbon fiber-reinforced surfaces provide more rigidity and truer flight. Final assembly is quick and easy, with no gluing — only a screwdriver and pliers are needed. You can choose the all-in-one convenience of the RTF version, or fly the Tx-R Prime version with a 4-channel SLT transmitter, or your favorite transmitter and the AnyLink2.

Recommended Products (Tx-R)

- TACJ2650 Tactic TTX650 6-Channel 2.4GHz SLT Computer Transmitter
 –or–
 FUTK6000 Futaba 6J 6-channel 2.4GHz S-FHSS Computer Radio System **and**
 TACJ2005 Tactic AnyLink2 2.4GHz Radio Adapter
 FLZA6024 Flyzone 11.1V 1800mah 20C LiPo Battery
 GPMM3318 ElectriFly AC/DC Balancing Smart Charger

Recommended Options (Tx-R)

- TACJ2404 Tactic TTX404 4-Channel 2.4GHz SLT Radio System
 TACJ2600 Tactic TTX600 6-Channel 2.4GHz SLT Radio System
 GPMM3155 ElectriFly AC/DC Triton EQ Balancing Charger
 SUPM0040 SuperTigre Adapter Deans® Ultra Plug® to SuperTigre ESC

Ask your hobby dealer for additional recommendations.

For more information on the AnyLink2, transmitter compatibility and requirements, see tacticrc.com/anylink2



FLZA3310

Wingspan: 49 in (1245 mm)
Weight: 38 oz (1075 g)
Length: 39.5 in (1005 mm)
Includes: Tactic TTX404 4-channel 2.4GHz SLT radio system, factory-installed SLT receiver, servos, 40A ESC & 30-24-920kV brushless outrunner motor, 11.1V 1800mAh LiPo battery, AC/DC balancing charger & (4) "AA" batteries
Requires: Nothing



FLZA3312

Weight: 38-42 oz (1075-1190 g)
Includes: factory-installed SLT receiver, servos, 40A ESC & 30-24-920kV brushless outrunner motor
Requires: 4-channel SLT transmitter –or– AnyLink2 & compatible 4-channel transmitter; 11.1V 1800mAh LiPo battery & LiPo charger



Deans and Ultra Plug are registered trademarks of W.S. Deans Co.