

mini Switch™



2 planes in 1

The Mini Switch lets you change between a low-wing and a high-wing mounting quickly and easily. Its compact size makes it easy to transport to and from the flight park without disassembling the plane.

The Mini Switch RTF includes a Tactic 2.4GHz radio, so you can be airborne in minutes. There's also a Tx-R Prime version you can fly with a 4-channel SLT transmitter, or your favorite radio and the Tactic AnyLink2. Experience the more flexible, and fun way to fly today with the Flyzone Mini Switch.

Recommended Products (Tx-R only)

TACJ2650	Tactic TTX650 6-Cchannel SLT Computer Transmitter - or -
FUTK6000	Futaba 6J 2.4GHz S-FHSS 6-Channel Computer Radio System <i>and</i>
TACJ2005	Tactic AnyLink2 2.4GHz Radio Adapter
FLZA6014	Flyzone 11.1V 1300 mAh Balanced LiPo Battery
GPMM3318	ElectriFly AC/DC Balancing Smart LiPo Charger

Recommended Options

GPMM3155 ElectriFly Triton EQ AC/DC Balancing Charger/Cycler/Discharger

Ask your hobby dealer for additional recommendations.

RTF
READY-TO-FLY

FLZA3320 – RTF

Wingspan (Low/High): 31 in (785 mm)/ 34 in (865 mm)

Length: 32.5 in (825 mm)

Weight: 20.4 oz (580 g)

Includes: high- and low-wing canopies, aluminum landing gear; Tactic TTX404 4-channel 2.4GHz SLT radio system; factory-installed 28-30-1100kV brushless outrunner motor, 20A ESC, micro servos & SLT receiver; 11.1V 1300mAh LiPo battery, AC/DC balancing charger & (4) "AA" batteries

Requires: Nothing!



Tx-R
PRIME

FLZA3322 – Tx-R

Wingspan (Low/High): 31 in (785 mm)/ 34 in (865 mm)

Length: 32.5 in (825 mm)

Weight: 20.4-21.2 oz (580-600 g)

Requires: 4-channel SLT transmitter - or - AnyLink2 and compatible 4-channel transmitter; 11.1V, 1300 mAh LiPo battery & LiPo charger