

F4U CORSAIR

outmaneuver the enemy



Flyzone makes it easy to fly the famous bent-wing fighter — AND includes exciting features, such as LED navigation lights and retracts, that most other Corsair models don't include. Choose the RTF for all-in-one convenience, or use your favorite transmitter with AnyLink to pilot the Tx-R. At a park or local club site, you'll win raves flying the Select Scale Corsair!

- Molded, factory-painted AeroCell foam sections assemble quickly, without glue.
- Both versions include brushless power system, five micro servos, and an SLT receiver compatible with AnyLink.
- Loaded with scale details — molded-in panel lines, pilot figure, replica radial engine, operating navigation lights and rotating retracts with gear doors.

Recommended Products (Tx-R)

TACJ2650	Tactic TTX650 6-Channel 2.4GHz SLT Computer Transmitter -or-
FUTK6000	Futaba 6J 6-channel 2.4GHz S-FHSS Computer Radio System <i>and</i>
TACJ2005	Tactic AnyLink2 2.4GHz SLT Radio Adapter
FLZA6173	Flyzone 11.1V 2100mAh Balanced LiPo Battery
GPMM3318	ElectriFly AC/DC Balancing Smart Charger

Recommended options (Tx-R)

GPMM3155	ElectriFly AC/DC Triton EQ Balancing Charger
SUPM0040	SuperTigre Adapter Star Plug to SuperTigre ESC

Ask your hobby dealer for additional recommendations.

For more information on the AnyLink2, transmitter compatibility and requirements, see tacticrc.com/anylink2.

Select Scale™ RTF
READY-TO-FLY

FLZA4030

Wingspan: 48.5 in (1230 mm)

Weight: 48 oz (1360 g)

Length: 38.5 in (980 mm)

Includes: Tactic TTX600 6-channel 2.4GHz SLT radio system, factory-installed 35-36-920kV brushless outrunner motor, 40A ESC, SLT receiver & micro servos; 11.1V 2100mAh balanced LiPo battery; DC balancing LiPo charger & (4) "AA" batteries

Requires: Nothing!

Select Scale™ Tx-R™
PRIME



FLZA4032

Wingspan: 48.5 in (1230 mm)

Weight: 48 oz (1360 g)

Includes: factory-installed 35-36-920kV brushless outrunner motor, 40A ESC, SLT receiver & micro servos

Requires: 5-channel SLT transmitter -or- AnyLink2 and compatible 5-channel transmitter, 11.1V 2100mAh LiPo battery & LiPo charger