

AXE™ 400

Brushless Mini Aerobats

**Fully assembled, factory
tested and 3D ready!**



With the Axe 400 3D, all-out 3D performance and absolute assembly ease are givens. All you need to do is choose between all-in-one completeness — and the freedom to equip the Axe 400 3D your way.

The **Rx-R™** gives you the option to choose the radio system you prefer, but includes all the performance pluses of the RTF: a brushless motor and ESC, plus a heading-hold gyro and Futaba servos. The **RTF** starts you out with the Futaba® 6EX — a 6-channel powerhouse built with interference-free FASST™ know-how.

RTF includes:

- Futaba 6EX 6-Channel 2.4GHz Computer Radio



Both versions are assembled, with:

- 425-size brushless motor
- Brushless electronic speed control
- HM4000 heading lock gyro
- (4) S3114 high-torque micro servos
- Efficient 120° eCCPM swash plate for smooth, precise aerobatics.
- 325 mm wood blades

MAIN ROTOR DIAMETER: 27.5 in (700 mm)

LENGTH: 24 in (610 mm)

WEIGHT: 21-25 oz (610-700 g)

BOTH REQUIRE: 11.1V LiPo battery pack, LiPo charger & 8 “AA” batteries. Rx-R also requires a 6-channel radio.

- HMXE0800 Axe 400 3D Brushless RTF
- HMXE0801 Axe 400 3D Brushless Rx-R

Recommended Products

- GPMP0406 ElectriFly® 11.1V 2000mAh Balanced LiPo Pack w/Deans® Ultra Plug® Connector

Recommended Options:

- GPMP0723 ElectriFly 11.1V 2300mAh BP Balanced 20C LiPo Pack w/Deans® Ultra Plug® Connector
- GPMP0520 ElectriFly 11.1V 2200mAh PS Balanced 25C LiPo Pack w/Deans® Ultra Plug® Connector

Note: For a complete list, see the instruction manual. Ask your hobby dealer for additional recommendations, or go to helimax-rc.com - where you'll also find the latest technical updates.

Deans® and Ultra Plug® are registered trademarks of W.S. Deans Co. U.S. Patent No. 5,533,915

Helix-Max®
helimax-rc.com

© 2011 Hobbico®, Inc., All rights reserved.