FS56-a The low-stress 4-stroke!

Everyone loves the sound and power of a 4-stroke, but no one likes the complex procedures that proper maintenance requires. That's why O.S. created the FS56-a. It's an engine with the power and performance of a 4-stroke matched to the maintenance ease and simplicity of a 2-stroke. Its tighter tolerances and advanced engineering result in an engine that's faster and easier to set up at the field and less maintenance-intensive over the long haul.

- More powerful than the FS-52 and more forgiving of minor maintenance lapses.
- Idle and valves are factory-adjusted to shorten setup and break-in.
- Reduces friction with dual bearings and resists wear with ringed ruggedness and strong conrod, wrist pin and valve assembly designs.
- A combination of tighter tolerances, a twin-needle carb and low-rpm operation help settings stay tight, minimizing the need for re-tuning.
- Improved venturi improves fuel/air mixing and minimizes the chances of fuel leaks.
- Lubrication system eliminates crankcase breather tube by recirculating excess oil back into the combustion chamber.
- F-4040 muffler can be rotated 360° and moved in or out. Exhaust outlet also rotates, giving you more mounting options. Helps keep scale looks intact and makes flex pipes unnecessary.
- Reversible carb and narrower camshaft housing ensure easier fits with fewer mods.
- Mounts in the same space as the FS-52, and features the same bolt pattern, hub position and linkage position.



Recommended Options:

	-
APCQ1207	APC LP12070 12x7 Sport Prop
APCQ1307	APC LP13070 13x7 Sport Prop
GPMG1061	Great Planes Adjustable Engine Mount 40-70
GPMP2022	Great Planes Standard ProGloW/Meter & Charger
GPMP3001	Great Planes After Run Engine Oil 2 Fl Oz
HCAP3205	Hobbico Panel-ReadyTorqMaster 90 Charger
HCAP3335	Safety Stick Engine Starter
TOPQ5140	12x6 Power Point Prop

See your favorite hobby retailer for additional recommendations.

Stock Number: OSMG0956 Specifications:

Specifications: Displacement: 0.569 in (9.32 cc) Bore: 0.945 in (24.0 mm) Stroke: 0.811 in (21 mm) RPM Range: 2400–13000 Output: 0.99 hp @ 10000 rpm Total Weight: 16.3 oz (460 g) Engine: 13.8 oz (419 g) Muffler: 1.48 oz (42 g) Includes: 40NA carb, F-4040 muffler assembly & F glow plug Requires: glow fuel & prop Suggested Props: 12x6-8, 13x6 & 13x7

All trademarks are the property of their respective owners.

