

# THIS OUTBOARD HAS THE EDGE OVER THE COMPETITION!

## .21XM V2 AIR-COOLED OUTBOARD MARINE ENGINE

Start with the race-proven .21XM, upgrade the cylinder head and muffler — and you've got the .21XM V2, the new marine powerhouse engine that's even faster than the original!

- The machined head is air-cooled, a simpler, more reliable system that insures optimum engine temperature under any conditions
- The muffler has been extended to generate more torque and power, while still being easy to tune and detachable
- With perfectly matched port timing, exhaust outlets, compression ratio and carb bore, the .21XM V2 is designed for competition, right out of the box
- The carburetor has both high-speed and mixture control needles
- A pressure line from the muffler sends a steady flow of lubricants to the flex drive system and bearings
- Prop height and angle can be adjusted independently
- Ball bearings minimize friction and wear for longer life and higher top-end speeds
- The bronze prop shaft assembly offers extreme durability
- A lightweight aluminum piston is performance-matched to a long-lasting ABN cylinder sleeve
- An exceptional value as well as a total competitive package, complete with a glow plug and carbon prop

### Recommended Products

- |                 |  |
|-----------------|--|
| <b>AQUP2230</b> | AquaCraft® Models 30% Boat Fuel (Quart)            |
| <b>FUTM0045</b> | Futaba® S3305 High-Torque Standard Servo           |
| <b>AQUB6903</b> | AquaCraft Models 3' Fuel Line (3/32" id, 3/16" od) |



### OSMG1720

**Displacement:** 0.211 cu in (3.46 cc)

**Bore:** 0.654 in (16.6 mm)

**Stroke:** 0.630 in (16.0 mm)

**Practical RPM:** 3,000-25,000

**Output:** 1.3 hp @ 25,000 rpm

**Weight:** 24.1 oz (682 g)

**Includes:** mount, outdrive unit, E-2050-2 removable muffler, starter cone, #20J carb, #8 glow plug, steering bracket, throttle link assembly & 42 x 1.2 carbon prop

**Requires:** 10-50% nitro boat fuel with at least 18% oil content

See your local dealer for additional recommendations.