

55HZ-R DRS RING

CONSISTENT HELI POWER



OSMG1957

Displacement: 0.55 cu in (8.93 cc)

Bore: 0.91" (23 mm)

Stroke: 0.85" (23.5 mm)

Practical RPM: 2,000-20,000

Output: 2.07 hp @ 17,000 rpm

Weight: 15.1 oz (429 g)

Includes: 55HZ-R DRS, #8 glow plug, check valve & instruction manual

Requires: 10-30% nitro fuel with a minimum of 18% lubricant

RECOMMENDED PRODUCTS

OSMG2691 O.S. Engine #8 Glow Plug

Laying down a hard core 3D flight requires time, talent and practice. It also requires consistency — and that's where the 55HZ-R DRS (Demand Regulator System) really shines.

Mounted in line with the carb, the DRS taps crankcase pressure to ensure a consistent flow of fuel from full tank to fumes, regardless of attitude. The result is superbly consistent performance and dependability second to none.

- 40L-R carb with high- and medium-speed needles and an idle mixture control screw provide fine-tuned performance through the rpm range.
- Push-pull throttle arm
- Dual bearings for smoother operation and less friction and wear
- Bolt-through mounts for tuned pipes
- Balanced, optimized crankshaft for vibration control and improved performance.
- Black-anodized, machined aluminum cylinder head and crankcase fins for extra cooling clearance.
- Durable ringed construction
- Same mounting bolt pattern as the 50SX-H Hyper and 55HZ.