

ANY LINK²

2.4GHz SLT RADIO ADAPTER

EVEN SIMPLER.
JUST AS
AFFORDABLE.
AND 8 WAYS
BETTER.

With the AnyLink2, you can fly any aircraft with a 2.4GHz SLT receiver – including all Tx-R (Transmitter-ready) aircraft – and fly them all with the transmitter you like best: yours. AnyLink2 makes it possible – and easier than ever before.

AnyLink2:

- 1) is a full-range device compatible with all SLT receivers. Great for gas giants, electric micros and more.
- 2) is compatible with even more transmitter brands, including many Airtronics models.
- 3) Includes a built-in LiPo battery good for 15 hours of flying time. Recharges in one on its own USB charger.
- 4) Includes 3 adapter cables, for instant compatibility with most transmitters.
- 5) Cables feature headphone-style plugs for easy installation and solid connections.
- 6) Sets up with push-button ease.
- 7) Attaches with dual locking strips, or a new clip that snaps on to metal carrying handles.
- 8) Does everything for less than the price of most 2.4GHz receivers.

TACJ2005

Dimensions: 2.70 x 1.50 x 0.98 in (68 x 37 x 25 mm)
Weight w/battery: 1.6 oz. (46 g)

AnyLink2 works with transmitters from:

- Airtronics®
- Futaba®
- Hitec®
- JR®
- Spektrum®
- Graupner®
- Walkera

Full Range!



Adapter Cables

The AnyLink2 includes three adapter cables (TACM0010-TACM0012*). Other adapter cables are available separately.

TACM0010	JR/Spektrum*
TACM0011	Futaba Square*
TACM0012	Spektrum DX6i/Hitec*
TACM0013	Futaba/Hitec Round
TACM0014	Airtronics SD Series
TACM0016	Airtronics 5-Pin Round

Note: adapter cables for the AnyLink and AnyLink2 are not interchangeable. AnyLink2 is compatible only with the cables above.

The AnyLink2 2.4GHz Radio Adapter is compatible with virtually all flight transmitters, regardless of brand, band or modulation. Transmitters must have a trainer or DSC jack. For more information on AnyLink2, transmitter compatibility or requirements, see the AnyLink2 Compatibility Chart on tacticrc.com. All trademarks are the property of their respective owners.



TACTIC
PURE RELIABLE 2.4