

Want to add flaps or other functions? The TTX610 makes it easy and affordable. Auxiliary functions can be activated simply by flipping the two-position or three-position switch. Plus, you can activate dual rates on the ailerons/elevator/rudder, with a simple flip of a switch.

The TTX610 offers 2.4GHz dependability and full compatibility with all SLT receivers –including the ones in all Tx-R (Transmitter-Ready) aircraft. That allows you to create an instantaneous and unbreakable link between your receiver and your transmitter in the time it takes to push a button.

Dependability, affordability and features make the TTX610 is a standout system that offers the features you want and room to grow!

Includes:

- Switched 5th and 6th channels for landing gear, flaps and other functions
- · Dual rate switch (aileron, elevator & rudder)
- Wireless trainer system, plus wired system with a 3.5mm round jack
- Digital trims with memory, fast/slow step adjustment & sound cues (Ch1-4)
- Servo reversing (all channels)
- V-tail and elevon mixing
- · Quad-bearing gimbals
- Adjustable stick lengths
- · Low-voltage & and no trainer signal alarms
- · Charge jack for optional rechargeable batteries
- Internal antenna
- Mode 1/Mode 2 selectable
- · On/off switch
- Factory-set fail-safes (aileron, elevator & rudder)
- User-settable throttle fail-safe
- Compact, lightweight TR625 twin antenna receiver with push-button linking



Recommended Products

DTXP4704 Duratrax Onyx "AA" Alkaline Batteries (4)DTXP4708 Duratrax Onyx "AA" Alkaline Batteries (8)

TACJ2610 TTX610 6-Channel SLT Radio

Specifications: Channels: 6

Frequencies: 2.403 – 2.480GHz

Modulation: FHSS spread spectrum

Input Power: (4) "AA" alkaline, NiCd or NiMH cells

(3.4-7.0V: not included)

Trainer Systems: Wireless (for Tactic radios with wireless trainer systems); wired (for all others)

