

TACTIC SERVOS

Exceptional values in powerful performance.

Tactic servos are solid buys in long-lasting performance and a pleasant surprise in value. From the ultralight 1.9-gram TSX1.9 to the tremendous, 188 oz.-in. TSX57, Tactic servos are a simple way to enjoy savings without sacrificing performance.

All Tactic servos are protected by a 1-year limited warranty. All (except TSX1.9) also include a universal connector and mounting hardware.

TACTICTM
PURE RELIABLE 2.4

SLTTM
SECURE LINK TECHNOLOGY

| Micro/Mini Servos | | | 4.8V | 4.8V | 6.0V | 6.0V | | |
|-------------------|-------------|-----------------------------------|----------------------------|-----------------|-------------------------|--------------|--|--------------------|
| Stock # | Description | Description | Torque | Speed | Torque | Speed | Dimensions | Weight |
| TACM0190 | TSX1.9 | 1.9g Micro CM | 2.35 oz-in (0.17 kg-cm) | 0.04 sec/60° | n/a | n/a | 0.79 x 0.55 x 0.24 in (20 x 14 x 6mm) | 0.07 oz (1.9 g) |
| TACM0205 | TSX5 | High-Speed Micro 1BB | 14 oz-in ((1.0)) | 0.11 sec/60° | 14 oz-in ((1.0)) | 0.09 sec/60° | 0.9 x 0.48 x 1.1 in (23 x 12 x 27 mm) | 0.32 oz (9 g) |
| TACM0210 | TSX10 | Digital High-Torque Micro 1BB, MG | 17 oz-in (1.2 kg-cm) | 0.12 sec/60° | 23 oz-in (1.7 kg-cm) | 0.10 sec/60° | 0.9 x 0.48 x 1.1 in (23 x 12 x 27 mm) | 0.48 oz (14 g) |
| TACM0220 | TSX20 | High-Speed Mini 2BB | 45 oz-in (3.2 kg-cm) | 0.16 sec/60° | 55 oz-in (4.0 kg-cm) | 0.13 sec/60° | 1.4 x 0.6 x 1.1 in (36 x 15 x 29 mm) | 0.88 oz (25 g) |
| TACM0225 | TSX25 | Digital High-Speed Mini CM, 2BB | 84 oz-in (6.1 kg-cm) | 0.15 sec/60° | 91 oz-in (6.6 kg-cm) | 0.12 sec/60° | 1.4 x 0.6 x 1.1 in (36 x 15 x 29 mm) | 0.88 oz (25 g) |

| Standard Servos | | | 4.8V | 4.8V | 6.0V | 6.0V | | |
|-----------------|-------------|----------------------------------|---------------------------|-----------------|---------------------------|--------------|---|------------------|
| Stock # | Description | Description | Torque | Speed | Torque | Speed | Dimensions | Weight |
| TACM0235 | TSX35 | Sport | 68 oz-in (4.9 kg-cm) | 0.18 sec/60° | 73 oz-in (5.3 kg-cm) | 0.16 sec/60° | 1.6 x 0.8 x 1.4 in (40 x 20 x 37 mm) | 1.3 oz (38 g) |
| TACM0240 | TSX40 | High-Speed 2BB MG | 93 oz-in (6.7 kg-cm) | 0.16 sec/60° | 99 oz-in (7.1 kg-cm) | 0.13 sec/60° | 1.6 x 0.8 x 1.5 in (40 x 20 x 38 mm) | 1.8 oz (51 g) |
| TACM0245 | TSX45 | High-Torque 2BB MG | 143 oz-in (10.3 kg-cm) | 0.21 sec/60° | 151 oz-in (10.9 kg-cm) | 0.17 sec/60° | 1.6 x 0.8 x 1.5 in (40 x 20 x 38 mm) | 1.8 oz (51 g) |
| TACM0247 | TSX47 | Digital High-Torque 2BB MG | 107 oz-in (7.7 kg-cm) | 0.21 sec/60° | 132 oz-in (9.5 kg-cm) | 0.16 sec/60° | 1.6 x 0.8 x 1.5 in (41 x 20 x 38 mm) | 1.8 oz (51 g) |
| TACM0255 | TSX55 | Ultra High-Torque 2BB MG | 181 oz-in (13.1 kg-cm) | 0.24 sec/60° | 203 oz-in (14.6 kg-cm) | 0.21 sec/60° | 1.6 x 0.8 x 1.5 in (41 x 20 x 38 mm) | 2.1 oz (58 g) |
| TACM0257 | TSX57 | Digital Ultra High-Torque 2BB MG | 176 oz-in (12.7 kg-cm) | 0.23 sec/60° | 188 oz-in (13.5 kg-cm) | 0.13 sec/60° | 1.6 x 0.8 x 1.5 in (40 x 20 x 38 mm) | 2.1 oz (58 g) |

Legend: BB = Ball Bearing(s); CM = Coreless Motor; MG = Metal Gear

TACTICTM
tacticrc.com

