



• Transmitter battery charge jack

• (1) High-torque SX-200 BB steering servo with

metal gears and (1) SX-100 standard servo

BRAKE DISKS For reliable and responsive stopping power.

ENCLOSED RADIO BOX Protects the factory-installed receiver and receiver battery

CV (CONSTANT VELOCITY) DRIVESHAFTS Reduce friction and backlash for more power at any

angle.

4-WHEEL SHAFT DRIVE Provides smooth, efficient handling and power.

FULLY ADJUSTABLE SUSPENSION Extensive shock, roll center, and camber link adjustments to improve handling and resist rollovers.



STEEL TURNBUCKLES HIGH-SPEED STEERING KIT Use the tight turning radius to cut Allow an infinite range of inside the competition. quick adjustments.



www.duratrax.com

RAPID-TUNE[™] ALUMINUM OIL SHOCKS (8) Factory-installed and filled, with adjustable spring tension for tuning. 63 possible shock mounting combinations to match any track or condition.

> DTXD71** Length: 22.375 in (568 mm) Width: 17 in (412 mm) Height (with body): 10.5 in (267 mm) Wheelbase: 14.375 in (365 mm) Track (F/R): 13.5 in (343 mm) Ground Clearance (fully extended): 3.75 in (95 mm) Weight: 10.8 lb (4.91 kg) Requires: 12 "AA" alkaline batteries, glow starter, glow fuel (O'Donnell® 20% Racing Fuel ODOP3320 recommended), 6-cell NiCd or NiMH pack and charger



DURABLE METAL GEARS Metal differential gears, bevel

INSTRUCTIONAL DVD Shows how to operate your engine and enjoy the RT-X 27! gears, drive pinion and ring gear.





Shuts down the engine instantly, without touching the flywheel or hot exhaust. SLIPPER CLUTCH Offers more cooling and traction control.



STEEL CLUTCH BELL & SPUR GEAR Durable steel construction for long-lasting performance.



3-SHOE RACING CLUTCH Inspired by 1/8 scale racing, A dedicated spring for each shoe ensures fast, positive engagement.

FAST, TWO-WAY STARTING! Use the included, hand-held Kwik-Pit[™] Super Start[™] RTR for quick shaft starting. An easy-access flywheel also lets you bump-start with a starter box



ALUMINUM TUNED **DUAL-CHAMBER** RACING PIPE

MOUNTED AND GLUED TRUGGY TIRES Factory-installed foam inserts.

TRUGGY WHEELS 17 mm hubs, compatible with other 1/8 scale racing truggy wheels and tires.







ALUMINUM CHASSIS Rigid 1/8" (3.2 mm) 7075 T6 aluminum side plates secure and protect on-board components.

SIDE PLATES





SUPERTIGRE® 4.4 CC **G-27CS RACING ENGINE™** This roaring big block engine puts a massive 2.5 hp at your command.







FUEL LINE CLAMP ADJUSTABLE STEEL