

ElectriFly™
by Great Planes®

**“Sparking Innovations
in Electric Flight.”™**

ELECTROSTIK™

Electric-Powered Sport Plane



Expertly
Covered with
MONOKOTE®

The tried and true Stik — now as an easy electric!

For many years the Stik design has been a staple at the flying field, and now ElectriFly has equipped it with clean, quiet electric power! Glow pilots considering an electric aircraft will find familiarity in the ElectroStik's quality wood construction and traditional look. Modelers who enjoy the advantages of brushless motors have the opportunity to experience flying an R/C classic. And everyone will appreciate how easy it is to get to the flight line — especially with the Receiver-Ready (Rx-R) version!



ARF



GPMA1574

Rx-R



GPMA7500



GPMA1574/ARF; GPMA7500/Rx-R
Wingspan: 52.75 in (1340 mm)
Wing Area: 589 in² (38 dm²)
Weight: 3-3.5 lb (1360-1587 g)
Wing Loading: 11.7-13.6 oz/ft² (36-42 g/dm²)
Length: 45.5 in (1155 mm)
Both require: 4-channel radio, receiver, 11.1V
3200mAh LiPo battery, charger
ARF also requires: 3 micro servos, out-runner
brushless motor, 45A brushless ESC

A low parts count and high level of preassembly means that the ElectroStik ARF can be flight-ready in just two hours. The preinstalled motor, ESC and servos in the Rx-R version cuts that time in half!

For the location of the nearest dealer, visit www.electrifly.com
or call 1-800-682-8948 and mention code number 99G38.

www.electrifly.com

ELECTROSTIK™

Electric-Powered Sport Plane



No gluing or measuring! The horizontal and vertical stabs simply bolt together.



The wing attaches quickly with these two streamlined thumb screws — no tools required!



A powerful RimFire 42-40-1000 out-runner brushless motor is already in place on the ElectroStik Rx-R, and is easy to mount in the ARF version.



Quality ElectriFly micro servos are included and installed in the Rx-R version and ready to be hooked up to the receiver.

Recommended for the ElectroStik Rx-R:

Futaba® R607FS 7-Channel 2.4GHz Receiver



Incredibly small and lightweight, this state-of-the-art receiver boasts all of the advantages of 2.4GHz spread spectrum technology. FUTL7637

ElectriFly Power Series 11.1V 3200mAh Balanced LiPo Battery Pack



Balancing allows each cell to reach a full 4.2V charge for more power. A 20C discharge rate helps keep cells cool under sustained loads. GPMP0623


ElectriFly Triton™ 2 Charger, Discharger & Cycler



One of the simplest — and most sophisticated — battery accessories ever, with amazing adjustability, versatility and programming ease. GPMM3153

Included with the ElectroStik Rx-R and recommended for the ElectroStik ARF:

ElectriFly RimFire™ 42-40-1000 Out-runner Brushless Motor



An extremely high power-to-weight ratio makes this the ideal choice for the ElectroStik. Tightly wrapped windings push efficiency up to 77%. GPMG4675

ElectriFly SS45 Brushless ESC



Hooks up in seconds, and delivers superbly smooth, precise response throughout the throttle range. Comes with Dean's® connectors. GPMM1840

ElectriFly ES80 Micro Servo



Delivers exceptional torque and speed, and weighs only 0.6 ounces. GPMM1220