

Heli-MAX™

Kinetic 50™

Almost-Ready-to-Fly
Nitro R/C Helicopter



**From smooth & stable
to extreme maneuvers!**



Even a beginner can get into heli flying with this impressive model — and experienced pilots will really appreciate the Kinetic 50 ARF's 3-D aerobatic capabilities, right out of the box. Compare features, price point, parts availability and aftermarket support, and you'll see that the Kinetic 50 has it all over the competition!

- **Large dimensions make the Kinetic 50 easy to track and very stable when hovering.**
- **Can be flown outside in virtually any wind conditions.**
- **Nitro power offers long flight times, quick re-fueling and consistent power.**

Kinetic 50™

Almost-Ready-to-Fly
Nitro R/C Helicopter

**Equip your
Kinetic 50
with the best
accessories!**

Recommended Required Accessories



**O.S.® SX-H Ringed
Hyper Heli Engine**
(OSMG1951)



**Futaba®
6EXH FM Radio**
(FUTK58**)



**Futaba
GY240 Gyro**
(FUTM0809)



**Futaba
S3151 Servo**
(FUTM0310)



**Hobbico® NiMH
4.8V 2000mAh
4.5A Battery Pack**
(HCAM6320)

Suggested High Performance Upgrades



**Futaba 9C Super
FM Heli Radio**
(FUTK76**)



**Futaba S9252
(FUTM0222) and
S9254 (FUTM0224)
Digital Servos**



**Futaba GY401 (FUTM0808) or
GY611 (FUTM0825) Gyro**



**Hobbico NiMH
4.8V 4200mAh
sub-C Battery Pack**
(HCAM6335)

We're behind you every step of the way!

- **Exceptional parts support — to get you back in the air quicker.**
- **Simple to assemble and maintain.**
- **Consumer-friendly packaging — making it easier for you to find the right aftermarket accessories.**
- **Product Support Hotline — for prompt, accurate answers to your technical questions.**

Call (217) 398-8970 and select Option 6 for Helicopter Support. It's open Monday-Friday 9 a.m.-5 p.m. Central Time. E-mail us at helihotline@hobbico.com.

For the location of the dealer nearest you, visit our website at www.helimax-rc.com, or call 1-800-682-8948 and mention code number 99F35.

www.helimax-rc.com

Heli-Max

Heli-Max™

Kinetic 50™

Almost-Ready-to-Fly
Nitro R/C Helicopter



The Kinetic 50 boasts a durable, reliable hex system, along with a self-aligning clutch.



Smooth flight characteristics are courtesy of a precision no-play swash plate with metal ball joints. Another performance feature is the 6 mm feathering spindle.




The torque tube-driven tail is powerful, efficient — and usually an expensive aftermarket accessory. But it's standard equipment on the Kinetic 50!



4 mm fly bar with large paddles

Tail-mounted rudder servo



Symmetrical 600 mm wood blades are included

Ball joints on both ends of the control rods

Large 500 cc fuel tank



Each tail rotor grip has dual ball bearings

The long tail boom will accommodate main blades of up to 620 mm

HMXE0250 Specifications

Rotor Diameter:	52.75 in (1340 mm)
Weight:	7.5 lb (3.4 kg)
Length:	47 in (1194 mm)
Width w/Landing Skids:	10 in (255 mm)
Height:	15.25 in (387 mm)
Gear Drive Ratio:	9.1:1/Main; 5:1/Tail

Requires: 6-channel heli radio w/5 servos; 46-51 cu in (7.5-8.0 cc) heli engine; .50-size muffler

Heavy-duty, wide stance landing gear

www.helimax-rc.com